











# **TESTED & CERTIFIED**

## MVB<sup>™</sup>3X by MIFRAM

ASTM - F2656-15

Tested & Certified at 5,513 lbs. @ 30 mph Penetration 31.83 ft Tested & Certified at 16,538 lbs. @ 31.06 mph Penetration 62.3 ft.

#### IWA 14-1:2013

Tested & Certified at 5,513 lbs. @ 30 mph Penetration 35.76 ft. Tested & Certified at 16,538 lbs. @ 20 mph Penetration 34.12 ft. Tested & Certified at 15,876 lbs. @ 30 mph Penetration 58.4 ft.

#### PAS 68:2013

Tested & Certified at 5,513 lbs. @ 30 mph Penetration 31.83 ft. Tested & Certified at 16,538 lbs. @ 20 mph Penetration 29.53 ft. Tested & Certified at 16,538 lbs. @ 30 mph Penetration 58.4 ft.

### ~667 KJ Energy Absorption

Absorption Equal to 89 Concrete blocks of 1 M<sup>3</sup> [2.4 Ton - 5,292 lbs.] Movement for 1 M Distance 16,538 lbs. @ 31 mph









AST trailers are made in the United States and comply with US DOT regulations. Each trailer is specially designed to safely store and transport the MVB3X system inventory. Built with ease of use in mind, every complete system includes the specific number of MVB3X barriers, appropriate size trailer and the accessories to meet your operational requirements.







